


过渡接头 ADAPTER



90°弯美制JIC外螺纹74°外
锥 / SAE外螺纹带O形圈轻系列ISO 11926-3
90° ELBOW JIC MALE 74° CONE / SAE
O-RINGBOSS L-SERIES ISO 11926-3

1J09-OG

代号 PART NO.	螺 纹 THREAD		O 形圈 O-RING		尺 寸 DIMENSIONS				
	E	F		F 端	A	B	S1	S2	
1J09-04-03OG	7/16"X20	3/8"X24		O903	24.5	28	11	14	
1J09-04OG	7/16"X20	7/16"X20		O904	24.5	27.2	11	17	
1J09-04-05OG	7/16"X20	1/2"X20		O905	26.6	29.9	14	17	
1J09-04-06OG	7/16"X20	9/16"X18		O906	26.6	31.8	14	19	
1J09-05-04OG	1/2"X20	7/16"X20		O904	26.6	30	14	17	
1J09-05OG	1/2"X20	1/2"X20		O905	26.6	29	14	17	
1J09-05-06OG	1/2"X20	9/16"X18		O906	26.6	31.8	14	19	
1J09-06-04OG	9/16"X18	7/16"X20		O904	26.9	30	14	17	
1J09-06-05OG	9/16"X18	1/2"X20		O905	26.9	29.9	14	17	
1J09-06OG	9/16"X18	9/16"X18		O906	26.9	31.8	14	19	
1J09-06-08OG	9/16"X18	3/4"X16		O908	30	36.8	19	24	
1J09-08-04OG	3/4"X16	7/16"X20		O904	32	33	19	17	
1J09-08-06OG	3/4"X16	9/16"X18		O906	33	33.5	19	19	
1J09-08OG	3/4"X16	3/4"X16		O908	33	36.8	19	24	
1J09-08-10OG	3/4"X16	7/8"X14		O910	34.8	44	22	27	
1J09-08-12OG	3/4"X16	1.1/16"X12		O912	37.9	51	27	32	
1J09-10-08OG	7/8"X14	3/4"X16		O908	38	40	22	27	
1J09-10OG	7/8"X14	7/8"X14		O910	37.8	44	22	27	
1J09-10-12OG	7/8"X14	1.1/16"X12		O912	41	51	27	32	
1J09-12-08OG	1.1/16"X12	3/4"X16		O908	45	44	27	24	
1J09-12-10OG	1.1/16"X12	7/8"X14		O910	44.2	47	27	27	
1J09-12OG	1.1/16"X12	1.1/16"X12		O912	44.2	51	27	32	
1J09-12-16OG	1.1/16"X12	1.5/16"X12		O916	47.8	54.5	33	41	
1J09-14OG	1.3/16"X12	1.3/16"X12		O914	47.5	53	30	36	
1J09-14-16OG	1.3/16"X12	1.5/16"X12		O916	48.5	54.5	33	41	
1J09-16-12OG	1.5/16"X12	1.1/16"X12		O912	48.8	54.5	33	32	
1J09-16-14OG	1.5/16"X12	1.3/16"X12		O914	49	56	33	36	
1J09-16OG	1.5/16"X12	1.5/16"X12		O916	48.8	54.5	33	41	
1J09-16-20OG	1.5/16"X12	1.5/8"X12		O920	53.8	59	41	50	
1J09-20-16OG	1.5/8"X12	1.5/16"X12		O916	55.5	59.5	41	41	
1J09-20OG	1.5/8"X12	1.5/8"X12		O920	55.3	59	41	50	
1J09-20-24OG	1.5/8" X12	1.7/8"X12		O924	59.4	63	48	55	
1J09-24OG	1.7/8"X12	1.7/8"X12		O924	62.5	63	48	55	
1J09-32OG	2.1/2"x12	2.1/2"x12		O932	80	76	63	70	

注： 1 螺母及衬套需另行订货。管子直径 D 为公制时，配用螺母及衬套分别选用 NB200、NB500。管子直径为英制时，配用螺母及衬套分别选用 NB200、NB300。2 F 端与 ISO 11926-1 油口相配。 Note: 1 Nut and sleeve should be ordered separately. The nut NB200 and sleeve NB500 is suitable for metric tube, the nut NB200 and sleeve NB300 is suitable for inch tube. 2 F end is connected with ISO 11926-1 port.